GJack`

TECHNICAL DATA SHEET

Design | Manufacture | Supply

Bartons Bank Branston Collection

15/5x70x280mm / Unfinished / Brushed / Rustic Grade / Micro Bevelled / Herringbone



INSTALLATION METHODS

Fully Bonded	Yes (recommended)
Nailed	Yes
Floated on underlay	Yes
Over Underfloor Heating	Yes (see below*)

*The underfloor heating system must have an even temperature over the entire floor surface. The sub floor temperature that the floor boards are sitting on cannot exceed 27°c. The heating system must be working two weeks prior to install. Once the floor is installed, acclimatise the wood flooring by turning the heating temperature up 1°c per day (18-27°c) then back down 1°c per day. This is to not shock the wood, which can cause cracking and shrinking.

GRADING CRITERIA

Rustic grade oak comes with all the variations and authentic characteristics familiar with this grade of wood. Featuring colour variations, grain pattern variations, unlimited knots size, cracks and splits.

PRODUCT DETAILS

Jank Hardness Rating:II20 lbf(4980N)Formaldehyde Emission:EI(EN717-1)Pentachlorophenol Emission:<5ppm(CEN/TR 14823)		
Formaldehyde Emission:El(EN717-1)Pentachlorophenol Emission:<5ppm(CEN/TR 14823)Reaction to Fire Certification:Cfl=sl(EN13501-1)Thermal Conductivity:NPDConstruction:EngineeredSpecie:European Oak (Quercus Robur)Pattern:1-stripProcess:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:Simm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:ISmmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Responsible Certification:	Please ask a member of staff for details
Pentachiorophenol Emission:<5ppm(CEN/TR 14823)Reaction to Fire Certification:Cfl-sl(ENI3501-1)Thermal Conductivity:NPDConstruction:EngineeredSpecie:European Oak (Quercus Robur)Pattern:1-stripProcess:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:Sm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:ISmmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Janka Hardness Rating:	1120 lbf(4980N)
Reaction to Fire Certification:Cfl-sl(ENI3501-1)Thermal Conductivity:NPDConstruction:EngineeredSpecie:European Oak (Quercus Robur)Pattern:1-stripProcess:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:5mm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Formaldehyde Emission:	E1(EN717-1)
Thermal Conductivity:NPDConstruction:EngineeredSpecie:European Oak (Quercus Robur)Pattern:1-stripProcess:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:Smm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodMidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Pentachlorophenol Emission:	<5ppm(CEN/TR 14823)
Construction:EngineeredSpecie:European Oak (Quercus Robur)Pattern:I-stripProcess:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:Smm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:ISmmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Reaction to Fire Certification:	Cfl-s1(EN13501-1)
Specie:European Oak (Quercus Robur)Pattern:I-stripProcess:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:Smm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Thermal Conductivity:	NPD
Pattern:1-stripProcess:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:5mm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Construction:	Engineered
Process:BrushedFinish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:5mm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:KusticMaintenance:Comprehensive maintenance instructions and materials are available	Specie:	European Oak (Quercus Robur)
Finish:UV hardened oil 10% sheenProfile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:5mm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Pattern:	1-strip
Profile:T&GEdge Profile:4-Sided Bevelled EdgeTop Layer:5mm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Process:	Brushed
Edge Profile:4-Sided Bevelled EdgeTop Layer:5mm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Finish:	UV hardened oil 10% sheen
Top Layer:5mm European Oak (Quercus Robur)Backing:Birch and Poplar Mixed PlywoodThickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Profile:	T&G
Backing:Birch and Poplar Mixed PlywoodThickness:I5mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Edge Profile:	4-Sided Bevelled Edge
Thickness:15mmWidth:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Top Layer:	5mm European Oak (Quercus Robur)
Width:70mmLength:280mmPack Size:TBCGrade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Backing:	Birch and Poplar Mixed Plywood
Length: 280mm Pack Size: TBC Grade: Rustic Maintenance: Comprehensive maintenance instructions and materials are available	Thickness:	15mm
Pack Size: TBC Grade: Rustic Maintenance: Comprehensive maintenance instructions and materials are available	Width:	70mm
Grade:RusticMaintenance:Comprehensive maintenance instructions and materials are available	Length:	280mm
Maintenance: Comprehensive maintenance instructions and materials are available	Pack Size:	TBC
·	Grade:	Rustic
Slip Resistance: Wet PTV slip rating of 36+	Maintenance:	Comprehensive maintenance instructions and materials are available
	Slip Resistance:	Wet PTV slip rating of 36+

INSTALLATION AND WARRANTY

All JackEvie Wood Floor Collections floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. JackEvie Wood Floor Collections warranty only applies to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide. This technical data sheet was written by JackEvie Wood Floor Collections. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.

Unit 21, Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton WV10 7DZ