

TECHNICAL DATA SHEET

Derwent Road *Clad-it Collection*

12/3 70x120x190mm x 1900mm / Brushed / Rustic Grade



INSTALLATION METHODS

Fully Bonded	Yes (recommended)
Nailed	Yes
Floated on underlay	Yes
Over Underfloor Heating	Yes (see below*)

*The underfloor heating system must have an even temperature over the entire floor surface. The sub floor temperature that the floor boards are sitting on cannot exceed 27°C. The heating system must be working two weeks prior to install. Once the floor is installed, acclimatise the wood flooring by turning the heating temperature up 1°C per day (18-27°C) then back down 1°C per day. This is to not shock the wood, which can cause cracking and shrinking.

GRADING CRITERIA

Rustic grade oak comes with all the variations and authentic characteristics familiar with this grade of wood. Featuring colour variations, grain pattern variations, unlimited knots size, cracks and splits.

PRODUCT DETAILS

Responsible Certification:	Please ask a member of staff for details
Janka Hardness Rating:	1120 lbf(4980N)
Formaldehyde Emission:	E1(EN717-1)
Pentachlorophenol Emission:	<5ppm(CEN/TR 14823)
Reaction to Fire Certification:	Cfl-s1(EN13501-1)
Thermal Conductivity:	NPD
Construction:	Engineered
Specie:	European Oak (Quercus Robur)
Pattern:	1-strip
Process:	Brushed
Finish:	UV hardened oil 10% sheen
Profile:	T&G
Edge Profile:	4-Sided Scraped Edge
Top Layer:	3mm European Oak (Quercus Robur)
Backing:	Eucalyptus Plywood
Thickness:	12mm
Width:	70/120/190mm mixed
Length:	1900mm
Pack Size:	3.61m ²
Grade:	Rustic
Maintenance:	Comprehensive maintenance instructions and materials are available
Slip Resistance:	Wet PTV slip rating of 36+

INSTALLATION AND WARRANTY

All JackEve Wood Floor Collections floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. JackEve Wood Floor Collections warranty only applies to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by JackEve Wood Floor Collections. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.