

## **TECHNICAL DATA SHEET**

Design | Manufacture | Supply

# **Dorset Walk** Grange Collection

22x70x300mm / Unfinished / Tumbled Edges / Polished / Worn / Natural Grade / Solid Oak / Herringbone



#### **INSTALLATION METHODS**

Fully Bonded	Yes (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	No

#### **GRADING CRITERIA**

Natural grade includes variations in colour tone from plank to plank, with more noticeable markings such as knots, streaks, sapwood and fine cracks. The grading is perfect for owners who want a non-uniform, natural wood floor.

#### **PRODUCT DETAILS**

Responsible Certification: Please ask a member of staff for details  Janka Hardness Rating: 1120 lbf(4980N)  Formaldehyde Emission: E1(EN717-1)  Pentachlorophenol Emission: <5ppm(CEN/TR 14823)  Reaction to Fire Certification: Cf1-s1(EN13501-1)  Thermal Conductivity: NPD  Construction: Solid oak  Specie: European Oak (Quercus Robur)  Pattern: 1-strip  Process: Polished / worn  Finish: UV hardened oil 10% sheen  Profile: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available  Slip Resistance: Wet PTV slip rating of 36+		
Formaldehyde Emission: EI(EN717-1)  Pentachlorophenol Emission: <5ppm(CEN/TR 14823)  Reaction to Fire Certification: CfI-sI(EN13501-1)  Thermal Conductivity: NPD  Construction: Solid oak  Specie: European Oak (Quercus Robur)  Pattern: 1-strip  Process: Polished / worn  Finish: UV hardened oil 10% sheen  Profile: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Responsible Certification:	Please ask a member of staff for details
Pentachlorophenol Emission: <5ppm(CEN/TR 14823)  Reaction to Fire Certification: Cfl-sl(ENI3501-1)  Thermal Conductivity: NPD  Construction: Solid oak  Specie: European Oak (Quercus Robur)  Pattern: 1-strip  Process: Polished / worn  Finish: UV hardened oil 10% sheen  Proffle: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Janka Hardness Rating:	1120 lbf(4980N)
Reaction to Fire Certification:       Cfl-sl(EN13501-l)         Thermal Conductivity:       NPD         Construction:       Solid oak         Specie:       European Oak (Quercus Robur)         Pattern:       1-strip         Process:       Polished / worn         Finish:       UV hardened oil 10% sheen         Profile:       T&G left and right handed blocks         Edge Profile:       Tumbled Edges / Polished / Worn Edge         Wear Layer:       12mm         Backing:       N/A         Thickness:       22mm         Width:       70mm         Length:       300mm         Pack Size:       TBC         Grade:       Natural         Maintenance:       Comprehensive maintenance instructions and materials are available	Formaldehyde Emission:	E1(EN717-1)
Thermal Conductivity:  Construction:  Solid oak  Specie: European Oak (Quercus Robur)  Pattern: 1-strip  Process: Polished / worn  Finish: UV hardened oil 10% sheen  Profile: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Pentachlorophenol Emission:	<5ppm(CEN/TR 14823)
Construction:  Solid oak  Specie: European Oak (Quercus Robur)  Pattern: 1-strip  Process: Polished / worn  Finish: UV hardened oil 10% sheen  Profile: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Reaction to Fire Certification:	Cfl-s1(EN13501-1)
Specie: European Oak (Quercus Robur)  Pattern: 1-strip  Process: Polished / worn  Finish: UV hardened oil 10% sheen  Profile: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Thermal Conductivity:	NPD
Pattern:  Process:  Polished / worn  Finish:  UV hardened oil 10% sheen  Profile:  T&G left and right handed blocks  Edge Profile:  Tumbled Edges / Polished / Worn Edge  Wear Layer:  12mm  Backing:  N/A  Thickness:  22mm  Width:  70mm  Length:  300mm  Pack Size:  TBC  Grade:  Natural  Maintenance:  Comprehensive maintenance instructions and materials are available	Construction:	Solid oak
Process: Polished / worn  Finish: UV hardened oil 10% sheen  Profile: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Specie:	European Oak (Quercus Robur)
Finish:  Profile:  T&G left and right handed blocks  Edge Profile:  Tumbled Edges / Polished / Worn Edge  Wear Layer:  12mm  Backing:  N/A  Thickness:  22mm  Width:  70mm  Length:  300mm  Pack Size:  TBC  Grade:  Natural  Maintenance:  Comprehensive maintenance instructions and materials are available	Pattern:	1-strip
Profile: T&G left and right handed blocks  Edge Profile: Tumbled Edges / Polished / Worn Edge  Wear Layer: 12mm  Backing: N/A  Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Process:	Polished / worn
Edge Profile:  Tumbled Edges / Polished / Worn Edge  Wear Layer:  12mm  Backing:  N/A  Thickness:  22mm  Width:  70mm  Length:  300mm  Pack Size:  TBC  Grade:  Natural  Maintenance:  Comprehensive maintenance instructions and materials are available	Finish:	UV hardened oil 10% sheen
Wear Layer:12mmBacking:N/AThickness:22mmWidth:70mmLength:300mmPack Size:TBCGrade:NaturalMaintenance:Comprehensive maintenance instructions and materials are available	Profile:	T&G left and right handed blocks
Backing:N/AThickness:22mmWidth:70mmLength:300mmPack Size:TBCGrade:NaturalMaintenance:Comprehensive maintenance instructions and materials are available	Edge Profile:	Tumbled Edges / Polished / Worn Edge
Thickness: 22mm  Width: 70mm  Length: 300mm  Pack Size: TBC  Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Wear Layer:	12mm
Width:     70mm       Length:     300mm       Pack Size:     TBC       Grade:     Natural       Maintenance:     Comprehensive maintenance instructions and materials are available	Backing:	N/A
Length:     300mm       Pack Size:     TBC       Grade:     Natural       Maintenance:     Comprehensive maintenance instructions and materials are available	Thickness:	22mm
Pack Size:  Grade:  Natural  Maintenance:  Comprehensive maintenance instructions and materials are available	Width:	70mm
Grade: Natural  Maintenance: Comprehensive maintenance instructions and materials are available	Length:	300mm
Maintenance: Comprehensive maintenance instructions and materials are available	Pack Size:	TBC
	Grade:	Natural
Slip Resistance: Wet PTV slip rating of 36+	Maintenance:	Comprehensive maintenance instructions and materials are available
- F	Slip Resistance:	Wet PTV slip rating of 36+

### INSTALLATION AND WARRANTY

All JackEvie Wood Floor Collections floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. JackEvie Wood Floor Collections warranty only applies to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by JackEvie Wood Floor Collections. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.