




Jack & Evie

Design | Manufacture | Supply

Technical Specification

Kings Crescent
The Hollybush Collection



Specification

Construction	Engineered
Specie	European Oak (Quercus Robur)
Pattern	1-strip
Process	Brushed / Distressed / Filled Splits / Ties / Sunken Knots
Finish	UV hardened oil 10% sheen
Profile	Tongue and Groove
Edge Profile	Cobbled Worn Edges
Backing	Eucaluptus Plywood
Top Layer	4mm European Oak (Quercus Robur)
Thickness	15 mm
Width	90mm / 150mm / 240mm mixed
Length	2200mm (May include up to 25% shorter boards)
Pack Size	TBC
Grade	Rustic

Grading Criteria

Rustic grade oak comes with all the variations and authentic characteristics familiar with this grade of wood. Featuring colour variations, grain pattern variations, unlimited knots size, cracks and splits.

Technical Criteria

Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1120 lbf(4980N)
Formaldehyde Emission	E1(EN717-1)
Pentachlorophenol Emission	<5ppm(CEN/TR 14823)
Reaction to Fire Certification	Cfl-s1(EN13501-1)
Thermal Conductivity	NPD
Maintenance	Comprehensive instructions and materials are available
Slip Resistance	Wet PTV slip rating of 36+

Installation Methods

Fully Bonded	Yes (recommended)
Nailed	Yes
Floated on underlay	Yes
Over Underfloor Heating	Yes (see below*)

*The underfloor heating system must have an even temperature over the entire floor surface. The sub floor temperature that the floor boards are sitting on cannot exceed 27°C. The heating system must be working two weeks prior to install. Once the floor is installed, acclimatise the wood flooring by turning the heating temperature up 1°C per day (18-27°C) then back down 1°C per day. This is to not shock the wood, which can cause cracking and shrinking.

Installation and Warranty

All JackEvie Wood Floor Collections floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. JackEvie Wood Floor Collections warranty only applies to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by JackEvie Wood Floor Collections. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.

Need help with your flooring project?

Speak to our specialist team

Call us on **01902 791 327**

or email **info@jackeviecollections.com**

Jack Evie

Design | Manufacture | Supply